



TERRA

2700 SERIES

ELEVATIONS
CG-OF

		OPENING WIDTH							
		24 5/8 (625)	28 1/2 (725)	30 1/2 (775)	32 1/2 (825)	36 3/8 (925)	40 3/8 (1025)	48 1/4 (1225)	56 1/8 (1425)
OPENING HEIGHT	RO inches/mm OSM inches/mm	23 5/8 (600)	27 1/2 (700)	29 1/2 (750)	31 1/2 (800)	35 3/8 (900)	39 3/8 (1000)	47 1/4 (1200)	55 1/8 (1400)
	16 3/4 (425)								
	15 3/4 (400)								
	20 5/8 (525)								
	19 5/8 (500)								
	24 5/8 (625)								
23 5/8 (600)									
28 1/2 (725)									
27 1/2 (700)									
30 1/2 (775)									
29 1/2 (750)									
32 1/2 (825)									
31 1/2 (800)									

E = THESE WINDOWS MEET CANADIAN EGRESS REQUIREMENTS.



TERRA

2700 SERIES

ELEVATIONS

CG-OF

OPENING WIDTH

RO Inches/mm OS&T Inches/mm	24 5/8 (625)		28 1/2 (725)		30 1/2 (775)		32 1/2 (825)		36 3/8 (925)		40 3/8 (1025)		48 1/4 (1225)		56 1/8 (1425)	
	23 5/8 (600)		27 1/2 (700)		29 1/2 (750)		31 1/2 (800)		35 3/8 (900)		39 3/8 (1000)		47 1/4 (1200)		55 1/8 (1400)	
36 3/8 (925)																
35 3/8 (900)																
40 3/8 (1025)																
39 3/8 (1000)																
48 1/4 (1225)																
47 1/4 (1200)																
56 1/8 (1425)																
55 1/8 (1400)																
60 (1525)																
59 (1500)																

E = THESE WINDOWS MEET CANADIAN EGRESS REQUIREMENTS.



TERRA

2700 SERIES

ELEVATIONS

CG-OF

		OPENING WIDTH					
		(1525)	64 (1625)	71 7/8 (1825)	29 3/4 (2025)	83 5/8 (2125)	95 1/2 (2425)
OPENING HEIGHT	RO mm						
	OS/CM mm	59 (1500)	63 (1600)	70 7/8 (1800)	78 3/4 (2000)	82 5/8 (2100)	94 1/2 (2400)
16 3/4 (425)	15 3/4 (400)						
20 5/8 (525)	19 5/8 (500)						
24 5/8 (625)	23 5/8 (600)						
28 1/2 (725)	27 1/2 (700)						
30 1/2 (775)	29 1/2 (750)						
32 1/2 (825)	31 1/2 (800)						

E = THESE WINDOWS MEET CANADIAN EGRESS REQUIREMENTS.



TERRA

2700 SERIES

ELEVATIONS

CG-OF

OPENING WIDTH

RO Inches/mm OSA Inches/mm	64 (1625)		71 7/8 (1825)		78 3/4 (2000)		83 5/8 (2125)		95 1/2 (2425)	
	59 (1500)	63 (1600)	70 7/8 (1800)	78 3/4 (2000)	82 5/8 (2100)	94 1/2 (2400)				
36 3/8 (925)										
35 3/8 (900)	15090	16090	18090	20090	21090	24090				
40 3/8 (1025)										
39 3/8 (1000)	150100	160100	180100	200100	210100	240100				
48 1/4 (1225)										
47 1/4 (1200)	150120	160120	180120	200120	210120	240120				
56 1/8 (1425)										
55 1/8 (1400)	150140	160140	180140	200140	210140	240140				
60 (1525)										
59 (1500)	150150	160150	180150	200150	210150	240150				

E = THESE WINDOWS MEET CANADIAN EGRESS REQUIREMENTS.



TERRA

2700 SERIES

ELEVATIONS

CSH-V

OPENING WIDTH

RO inches/mm OSM inches/mm		16 3/4	20 5/8	24 5/8	28 1/2	30 1/2	32 1/2	36 3/8	40 3/8	48 1/4
		(425)	(525)	(625)	(725)	(775)	(825)	(925)	(1025)	(1225)
OPENING HEIGHT		15 3/4	19 5/8	23 5/8	27 1/2	29 1/2	31 1/2	35 3/8	39 3/8	47 1/4
		(400)	(500)	(600)	(700)	(750)	(800)	(900)	(1000)	(1200)
28 1/2 (725)	27 1/2 (700)									
30 1/2 (775)	29 1/2 (750)									
32 1/2 (825)	31 1/2 (800)									
36 3/8 (925)	35 3/8 (900)									
40 3/8 (1025)	39 3/8 (1000)									
48 1/4 (1225)	47 1/4 (1200)									
55 1/8 (1425)	55 1/8 (1400)									



TERRA

2700 SERIES

ELEVATIONS

CSH-V

OPENING WIDTH

		16 3/4	20 5/8	24 5/8	28 1/2	30 1/2	32 1/2	36 3/8	40 3/8	48 1/4
		(425)	(525)	(625)	(725)	(775)	(825)	(925)	(1025)	(1225)
		15 3/4	19 5/8	23 5/8	27 1/2	29 1/2	31 1/2	35 3/8	39 3/8	47 1/4
		(400)	(500)	(600)	(700)	(750)	(800)	(900)	(1000)	(1200)
OPENING HEIGHT	60 (1525)									
	59 (1500)	40150	50150	60150	70150	75150	80150	90150	100150	120150
	64 (1625)									
	63 (1600)	40160	50160	60160	70160	75160	80160	90160	100160	120160
	71 7/8 (1825)									
	70 7/8 (1800)	40180	50180	60180	70180	75180	80180	90180	100180	120180

E = THESE WINDOWS MEET CANADIAN EGRESS REQUIREMENTS.



TERRA

2700 SERIES

ELEVATIONS
CP-P

OPENING WIDTH

RO Inches/mm	OPENING WIDTH									
	16 3/4 (425)	20 5/8 (525)	24 5/8 (625)	28 1/2 (725)	30 1/2 (775)	32 1/2 (825)	36 3/8 (925)	40 3/8 (1025)	48 1/4 (1225)	56 1/8 (1425)
OSM Inches/mm	15 3/4 (400)	19 5/8 (500)	23 5/8 (600)	27 1/2 (700)	29 1/2 (750)	31 1/2 (800)	35 3/8 (900)	39 3/8 (1000)	47 1/4 (1200)	55 1/8 (1400)
16 3/4 (425)	4040	5040	6040	7040	7540	8040	9040	10040	12040	14040
20 5/8 (525)	4050	5050	6050	7050	7550	8050	9050	10050	12050	14050
24 5/8 (625)	4060	5060	6060	7060	7560	8060	9060	10060	12060	14060
28 1/2 (725)	4070	5070	6070	7070	7570	8070	9070	10070	12070	14070
30 1/2 (775)	4075	5075	6075	7075	7575	8075	9075	10075	12075	14075
32 1/2 (825)	4080	5080	6080	7080	7580	8080	9080	10080	12080	14080
36 3/8 (925)	4090	5090	6090	7090	7590	8090	9090	10090	12090	14090
40 3/8 (1025)	40100	50100	60100	70100	75100	80100	90100	100100	120100	140100
48 1/4 (1225)	40120	50120	60120	70120	75120	80120	90120	100120	120120	140120
56 1/8 (1425)	40140	50140	60140	70140	75140	80140	90140	100140	120140	140140



TERRA

2700 SERIES

ELEVATIONS

CP-P

OPENING WIDTH

R.O. inches/mm	OPENING WIDTH									
	16 3/4 (425)	20 5/8 (525)	24 5/8 (625)	28 1/2 (725)	30 1/2 (775)	32 1/2 (825)	36 3/8 (925)	40 3/8 (1025)	48 1/4 (1225)	56 1/8 (1425)
OSM inches/mm	15 3/4 (400)	19 5/8 (500)	23 5/8 (600)	27 1/2 (700)	29 1/2 (750)	31 1/2 (800)	35 3/8 (900)	39 3/8 (1000)	47 1/4 (1200)	55 1/8 (1400)
60 (1525)	40150	50150	60150	70150	75150	80150	90150	100150	120150	140150
64 (1625)	40160	50160	60160	70160	75160	80160	90160	100160	120160	140160
71 7/8 (1825)	40180	50180	60180	70180	75180	80180	90180	100180	120180	140180
73 3/4 (1875)	40200	50200	60200	70200	75200	80200	90200	100200	120200	140200
83 5/8 (2125)	40210	50210	60210	70210	75210	80210	90210	100210	120210	140210 *
84 1/2 (2100)	40240	50240	60240	70240	75240	80240	90240	100240	120240 *	140240 *

* = NOT AVAILABLE IN TRIPANE.



TERRA

2700 SERIES

ELEVATIONS
CP-P

OPENING WIDTH

OPENING HEIGHT

		OPENING WIDTH					
		60 (1525)	64 (1625)	71 7/8 (1825)	79 3/4 (2025)	83 5/8 (2125)	95 1/2 (2425)
		59 (1500)	63 (1600)	70 7/8 (1800)	78 3/4 (2000)	82 5/8 (2100)	94 1/2 (2400)
		<small> 16 3/4 (425) 15 3/4 (400) 20 5/8 (525) 19 5/8 (500) 24 5/8 (625) 23 5/8 (600) 28 1/2 (725) 27 1/2 (700) 30 1/2 (775) 29 1/2 (750) 32 1/2 (825) 31 1/2 (800) 36 3/8 (925) 35 3/8 (900) 40 3/8 (1025) 39 3/8 (1000) 48 1/4 (1225) 47 1/4 (1200) 56 1/8 (1425) 55 1/8 (1400) </small>					
		<small> 15040 16040 18040 20040 21040 24040 15050 16050 18050 20050 21050 24050 15060 16060 18060 20060 21060 24060 15070 16070 18070 20070 21070 24070 12075 16075 18075 20075 21075 24075 15080 15080 18080 20080 21080 24080 15090 16090 18090 20090 21090 24090 150100 160100 180100 200100 210100 240100 150120 160120 180120 200120 210120 240120 150140 160140 180140 200140 210140 240140 </small>					
16 3/4 (425)	15 3/4 (400)						
20 5/8 (525)	19 5/8 (500)						
24 5/8 (625)	23 5/8 (600)						
28 1/2 (725)	27 1/2 (700)						
30 1/2 (775)	29 1/2 (750)						
32 1/2 (825)	31 1/2 (800)						
36 3/8 (925)	35 3/8 (900)						
40 3/8 (1025)	39 3/8 (1000)						
48 1/4 (1225)	47 1/4 (1200)						
56 1/8 (1425)	55 1/8 (1400)						



TERRA

2700 SERIES ELEVATIONS CP-P

OPENING WIDTH

OPENING HEIGHT	OPENING WIDTH					
	60 (1525) 59 (1500)	64 (1625) 63 (1600)	71 7/8 (1825) 70 7/8 (1800)	79 3/4 (2025) 78 3/4 (2000)	83 5/8 (2125) 82 5/8 (2100)	95 1/2 (2425) 94 1/2 (2400)
60 (1525) 59 (1500)	150150	160150	180150	200150 *	210150 *	240150 *
64 (1625) 63 (1600)	150160	160160	180160 *			
71 7/8 (1825) 70 7/8 (1800)	150180	160180 *	180180 *			
79 3/4 (2025) 78 3/4 (2000)	150200 *	160200 *	180200 *			
83 5/8 (2125) 82 5/8 (2100)	150210 *	160210 *	180210 *			
95 1/2 (2425) 94 1/2 (2400)	150240 *					

* = NOT AVAILABLE IN TRIPANE.